

- ◆ 品牌：中联科创（ZLKC）
- ◆ 规格：4/3" C 型 f=12mm F2.8
- ◆ 多层镀膜，有效提高透过率
- ◆ 2000 万像素高品质影像
- ◆ 高对比度、大景深设计
- ◆ 畸变小于 0.1%
- ◆ 适用机器视觉,工业监控等

产品规格书：

2000 万像素 12mm 低畸变 FA 镜头 C Mount		物距 Working Distance	倍率 Optical Magnific ation	视野 4/3"Field of View(mm)		
型号 Model	KM1228MP20		X	H	V	
相机靶面 Image Size	4/3-inch		0.002X	7158.8	5369.1	
焦距 Focal length	12mm		0.006X	2883.7	2162.8	
光圈范围 F No.	F2.8-22		0.012X	1458.6	1094.0	
最短物距 M.O.D(m)	0.1-Inf.		0.013X	1316.1	987.1	
控制方式 Operation	Iris	Manual 手动调整	0.015X	1173.6	880.2	
	Focus	Manual 手动调整	0.017X	1031.1	773.4	
视场角 Angle of View (DxHxV)	4/3"	83.4°x71.2°x56.3°	0.020X	888.6	666.5	
	1"	66.1°x54.8°x42.3°	0.022X	817.4	613.0	
	2/3"	47.9°x38.9°x29.6°	0.024X	746.1	559.6	
畸变 Distortion	<1%		0.026X	674.9	506.2	
光学后焦 BFL	10.6mm		0.029X	603.6	452.7	
接口 Mount	C-Mount		0.033X	532.4	399.3	
近摄视野 Object Dimension	461.1mmx345.8mm(WD=300 mm)		0.038X	461.1	345.8	
外形尺寸 Dimension			250	0.045X	389.9	292.4
重量 Weight	245.0g		200	0.056X	318.6	238.9
滤镜尺寸 Filter Thread	—		150	0.072X	2470.7	